

## Product Display



## Description

The US200-4 was designed as a 4-way splitter to provide four signals of equal amplitude and phase.

## Specifications

### Connectors

Input..... 1 ea Type N Female

Output..... 4 ea Type N Female

Frequency Range..... 470-810 MHz

Max. Throughput Power..... 200W P-SYNC of 100W RMS Digital

Port to Port Isolation..... >15 dB

Height..... 1.0 in (24.5 MM)

Width..... 6.5 in (162 mm)

Length..... 8 in (224 mm)

Weight..... 2.2lbs (1.0kg)

Mounting Hardware..... The US200-4 comes in a rugged aluminum enclosure with mounting holes for mounting to a heat sink. A heat sink may be required if operating with maximum throughput power and elevated temperatures. This is not necessary if enclosure temperature does not exceed 60 Deg C.

Availability upon request. PTI does not guarantee to have all products in stock at time of order.

For bulk orders, please contact a PTI sales representative for pricing at 916-652-1116 or email at [sales@ptibroadcast.com](mailto:sales@ptibroadcast.com)

If you do not see the exact product or accessory that you are looking for, PTI has an expanded assortment of products including accessories and custom assemblies that are not listed online. Please contact PTI for requests concerning items not found on our website.

The information offered herein is subject to change without notice.